

GYT117 Siemens values for Yuasa battery types

	Normal Voltage	Normal Capacity (Ah)		Dimensions						GYT117 Healthy Fully Charged Conductance Readings
Model	(V)	(20Hr)	(10Hr)	L (mm)	W (mm)	Height over terminals (mm)	Weight Approx (Kg)	Layout	Terminal	Siemens
NP1-6	6	1	0.93	51	42.5	54.5	0.25	5	A	36
NP1.2-6	6	1.2	1.11	97	25	54.5	0.31	1	A	24
NP1.2-6S	6	1.2	1.11	97	25	54.5	0.31	1	A	24
NP2.8-6	6	2.8	2.6	134	34	64	0.57	1	A	48
NP3.6	6	3	2.78	134	34	64	0.63	1	A	76
NP4-6	6	4	3.7	70	47	105.5	0.85	5	A	92
NP4-6S	6	4	3.7	70	47	105.5	0.85	5	A	88
NP7-6	6	7	6.48	151	34	97.5	1.32	1	H	168
NP7-6S	6	7	6.48	151	34	97.5	1.32	1	H	150
NP10-6	6	10	9.25	151	50	97.5	1.93	1	A&C	240
NP10-6S	6	10	9.25	151	50	97.5	1.93	1	A&C	150
NP12-6	6	12	11.1	151	50	97.5	2.05	1	C	256
NP12-6SL	6	12	11.1	151	50	97.5	2.05	1	C	218
NP0.8-12	12	0.8	0.74	96	25	61.5	0.35	9	I	-
NP1.2-12	12	1.2	1.11	97	48	54.5	0.57	3	A	32
NP2-12	12	2	1.85	150	20	89/85	0.7	10	B	-
NP2.1-12	12	2.1	1.9	178	34	64	0.83	1	A	48
NP2.1-12S	12	2.1	1.9	178	34	64	0.83	1	A	48
NP2.3-12	12	2.3	2.13	178	34	64	0.94	1	A	60
NP2.3-12S	12	2.3	2.13	178	34	64	0.94	1	A	50
NP2.8-12	12	2.8	2.6	134	67	64	1.1	3	A	84
NP2.8-12S	12	2.8	2.6	134	67	64	1.1	3	A	36
NP3.2-12	12	3.2	3	134	67	64	1.17	4	A	64
NP3.2-12S	12	3.2	3	134	67	64	1.17	4	A	64
NP4-12	12	4	3.7	90	70	106	1.57	1	A&C	64
NP4-12S	12	4	3.7	90	70	106	1.57	1	A&C	64
NPH5-12	12	-	5	90	70	106	2	1	D	184
NP7-12	12	7	6.48	151	65	97.5	2.65	4	A&C	160
REC10-12	12	10	9.3	151	65	97.5	3.4	4	C	192
NP12-12	12	12	11.1	151	98	97.5	4.09	4	D	272
NP17-12	12	17	13.88	181	75	167	6.2	2	J&E	360
NPC17-12	12	17	13.88	181	75	167	6.2	2	J&E	328
NP24-12	12	24	22.2	166	175	125	8.92	2	J&E	488
NP24-12S	12	24	22.2	166	175	125	8.92	2	J&E	215
NPC24-12	12	24	22.2	166	175	125	8.92	2	J&E	504
RE7-12	12	7	6.48	151	65	97.5	2.65	4	A&C	168