Yuasa Scheda Tecnica

Yuasa YBX5068 - Batterie YBX5000 Silver High Performance SMF

Prestazione

Tensione	12V
Capacità (20 ore)	75Ah
Corrente di spunto A (EN1)	650A



Dimensioni

Lunghezza	269mm
Profondità	174mm
Altezza	225mm

Pesi e Misure

Peso medio con acido	18.1kg

Caratteristiche del Monoblocco


Tipo di monoblocco	JIS D26 + B5
Fissaggi alla base	B5
Indicatore dello stato di carica	✔
Maniglie	✔
Circuito di sfiato	✔
Tipo di coperchio	Doppio Coperchio SMF

Tecnologia


Pastiglia antideflagrante	✔
Tecnologia	Ca/Ca
Separatore	PE
Test antiribaltamento VDA	✔
Corrente di carica raccomandata	4A
Performance Marking	W4-C2-V3-E1

Tipologia dei terminali


T1
Standard DIN Post



Schema di Collegamento



Fissaggio batteria



Scheda tecnica prodotta su E&OE

Yuasa Technical Data Sheet

Yuasa YBX5068 - YBX5000 Silver High Performance SMF Batteries

Performance

Voltage	12V
Capacity (20-hour)	75Ah
Cold Cranking Amps (EN1)	650A



Dimensions

Length	269mm
Width	174mm
Height	225mm

Weights & Measures

Mean Weight with Acid	18.1kg

Container Features


Case Type	JIS D26 + B5
Hold Down	B5
State of Charge Indicator	✔
Handles	✔
End Venting	✔
Lid Type	SMF Double Lid

Technology


Flame Arrestor	✔
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✔
Recommended Charge Rate	4A
Performance Marking	W4-C2-V3-E1

Terminal Type


T1
Standard DIN Post



Cell Assembly Layout



Battery Hold-down



Data Sheet generated on 28/03/2024 – E&OE